

## KT-Degreaser

### STOCK POINTS

### Characteristics & Applications

- Emulsifying tank cleaning agent based on hydrocarbon solvents
- Contains surface active agents
- Specific solvent with high boiling point and flash point
- Ideally suitable for removal of Black Fuel Oils, Heavy Lube Oils, Lube Oil Additives and Waxes.
- Can be used diluted 2-5% at temperatures up to 80°C.

### Waste Water Information

- Contains biodegradable surface active agents and hydrocarbon solvents
- Approved by MARPOL/IMO in accordance with MEPC.1/Circ.590

### Tank Material

- Safe to use on epoxy, polyurethane, zinc-silicate coatings and stainless steel ([see resistance tests](#))

### Properties

- Phys. properties : yellowish clear liquid.
- Flash point : 65 deg.C
- PH Value : neutral (solvent mixture)
- Spec. gravity : approx. 0,9
- Storage temp. : -10 to +30 deg C °
- Foam formation : slightly foaming
- Solubility in water : emulsifying in water

### Safety Aspects

- Ventilate tank sufficiently before entry.
- Consult Material Safety Data Sheet.

### Application for use

- Suitable in fresh water and seawater
- Recommended concentration for re-circulation cleaning : 2 - 5%
- Cleaning temperature : 60-80 deg.C.

### Packing

- Canister of 20-25 ltr and drums of 200-208 ltr.
- Product needs to be packed in steel drums. Please store the steel drums at a dry place to avoid corrosion.

**Asia:**  
Singapore  
Ulsan

**China:**  
Tianjin  
Shanghai  
Guangzhou

**Europe:**  
Algeciras  
Amsterdam  
Antwerp  
Augusta  
Genoa  
Hamburg  
Istanbul  
Kiel  
Marseille  
Rotterdam

**Middle East:**  
Dubai  
Mumbai  
Kandla  
Port Said/Suez

**South Africa:**  
Durban  
Cape Town  
Port Elizabeth

**South America:**  
Panama  
Buenos Aires  
Montevideo  
Porto Alegre  
Santos

**U.S.A.:**  
Houston  
New York